

## PoE 4Port, Uplink 1port

# WG-SH504





### → 제품특징

- PoE 4Port / Uplink 1port
- 모든 포트 Gigabit 통신
- PoE 최대 60W
- PoE 와치독 (자동복구)
- Hi-PoE (60W) 지원

### → 외관도

단위: mm



### → 주요사항

#### Hardware Feature

Ethernet Port	Port1-4: 4 × RJ-45 10/100/1000M (PoE) Port5: 1 × RJ-45 10/100/1000M (uplink)
---------------	---

PoE Power Consumption	Port1 ≤ 60 W max (Hi-PoE) Port2-4 ≤ 30 W max Total ≤ 60 W
-----------------------	---

Power Consumption	Idling: 0.96 W Full load: 60 W
-------------------	-----------------------------------

Standard	IEEE802.3, IEEE802.3u, IEEE802.3ab, IEEE802.3x
----------	--

#### PoE

PoE Standard	IEEE802.3af/ IEEE802.3at/ Hi-PoE
--------------	----------------------------------

PoE Pin Assignment	1, 2, 4, 5 (V+), 3, 6, 7, 8 (V-)
--------------------	----------------------------------

Long Distance PoE	100 m long distance PoE transmission
-------------------	--------------------------------------

PoE Power Management	Yes
----------------------	-----

PoE Watchdog	Yes
--------------	-----

#### Performance

Switching Capacity	14 Gbps
--------------------	---------

Packet Forwarding Rate	8,928 Mbps
------------------------	------------

Packet Buffer Memory	1 Mbit
----------------------	--------

MAC Address Table	2 K
-------------------	-----

Jumbo Frame	9KByte
-------------	--------

Working Temperature	-10 °C to 55 °C (+14°F to +131°F)
---------------------	-----------------------------------

Operating Humidity	5%~95% (RH)
--------------------	-------------

#### General

Power Input	48 V - 57 V DC
-------------	----------------

Lighting Protection	Common mode: 8 kV Differential mode: 4 kV
---------------------	--

ESD Protection	Air discharge: 15 kV Contact discharge: 10 kV
----------------	--

Wall-mount Installation	Yes
-------------------------	-----

Anti-theft Lock Hole	Yes
----------------------	-----

Weight	0.30 kg
--------	---------

Dimension	130 mm × 85 mm × 26 mm
-----------	------------------------